



บริษัท น้ำมันอพลโล (ไทย) จำกัด
APOLLO (THAILAND) CO., LTD.



DAAPHNE TURBINE OIL SERIES

High Performance Turbine Oil

1. Application

This oil suits best for high speed bearings of steam, marine and various gas turbines as well as blowers, pumps, electric motors and centrifugal refrigerators. And also oil unification standpoint of view, this oil serves for generic hydraulic fluid.

2. Quality

High quantity “multi-inhibited” type turbine oil, refined by most advanced process hydro-treating process, with various additives.

3. Characteristics

This oil is outstanding in respect of oxidation stability, rust preventive properties and anti-foam characteristics, so it stand long continuous operation as well as to keep good water separation property and low temperature fluidity.

4. Typical Specification

			<u>32</u>	<u>46</u>	<u>56</u>	<u>68</u>	<u>100</u>	<u>ASTM</u>
Specific Gravity	15/4	°C	0.863	0.870	0.87	0.872	0.88	D1298
Color	ASTM		L0.5	L0.5	L0.5	L0.5	L0.5	D1500
Flash Point	C.O.C.	°C	226	234	238	246	250	D92
Viscosity	@ 40°C	cSt	31.27	46.15	55.73	66.6	98.6	D445
Acid Number		mgKOH/g	0.10	0.08	0.07	0.08	0.08	D974
Copper Corrosion	100°Cx3	1(1a)	1(1b)	1(1b)	1(1b)	1(1b)	1(1b)	

- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or E-Mail : order@apollothai.com
- Due to continual product research and development, the information contained herein is subject to change without notification.

นิคมอุตสาหกรรมอมตะซิตี้ ชลบุรี 700/623 หมู่ที่ 4 ต.บ้านเก่า อ.พานทอง จ. ชลบุรี 20160 โทร. 0-3845-6900 แฟกซ์ 0-3821-0055

Amatanacity Chonburi Industrial Estate 700/623 Moo 4,Bankao, Panthong, Chonburi 20160 Tel : 038-456-900 Fax : 038-210-055 www.apollothai.com